

MONO

POLY



HELIENE

72M-BLK

72-CELL MONOCRYSTALLINE MODULE



345 Wp

MAX POWER OUTPUT

18.0%

MAX EFFICIENCY

10 YEAR

PRODUCT WARRANTY

25 YEAR

LINEAR PERFORMANCE GUARANTEE



H-BLACK INTEGRATION - BLACK FRAME & BACKSHEET



PERFECT FOR HIGH VISIBILITY APPLICATIONS



MANUFACTURED ACCORDING TO INTERNATIONAL QUALITY SYSTEM STANDARDS: ISO9001



GUARANTEED POSITIVE POWER SORTING: [-0 : +4.99 WP]


HELIENE INC. IS A PREMIER SOLAR MODULE MANUFACTURER, SERVICING THE GROWING SOLAR ENERGY MARKETS OF NORTH AMERICA.

COMBINING PROVEN EUROPEAN TECHNOLOGY WITH NORTH AMERICAN INGENUITY ALLOWS HELIENE TO MAKE A REAL COMMITMENT IN PROVIDING SMARTER ENERGY CHOICES FOR THE FUTURE.


Heliene Inc.
www.heliene.com

LINEAR PERFORMANCE GUARANTEE



10 YEAR WORKMANSHIP WARRANTY • 25 YEAR LINEAR PERFORMANCE GUARANTEE



DIMENSIONS FOR HELIENE 72M SERIES MODULES



I-V CURVE FOR HELIENE 72M SERIES



CERTIFICATIONS



ELECTRICAL DATA (STC)

Peak Rated Power	P_{mpp} (W)	345	340	335	330
Maximum Power Voltage	V_{mpp} (V)	38.84	38.50	38.21	37.96
Maximum Power Current	I_{mpp} (A)	8.95	8.89	8.83	8.76
Open Circuit Voltage	V_{oc} (V)	47.26	46.95	46.64	46.31
Short Circuit Current	I_{sc} (A)	9.57	9.49	9.41	9.34
Module Efficiency *	Eff (%)	18.0	17.8	17.5	17.3
Power Output Tolerance		[- 0 , + 4.99] Wp			

STC - Standard Test Conditions: Irradiation 1000 W/m² - Air mass AM 1.5 - Cell temperature 25 °C

* Calculated using maximum power based on full positive output tolerance [-0 , +4.99] Wp

MECHANICAL DATA

Dimensions (L x W x D)	1956 x 992 x 40 mm (77 x 39 x 1.6 inch)
Weight	21 kg (46.3 lbs)
Output Cables	1.1 m (43.3 inch) symmetrical cables with MC4 type connectors
Junction Box	IP-67 rated with 3 bypass diodes (IP-67 Available upon request)
Frame	Double webbed 15 micron anodized aluminum alloy
Front Glass	Low-iron content, high-transmission PV solar glass
Solar Cells	72 Monocrystalline cells (156 x 156 mm)

CERTIFICATIONS

UL Listed	ULC/ORD-C1703-1 , UL1703, UL1703 Fire Classification Type 1
IEC Listed	IEC 61215, IEC 61730

All Heliene modules are certified under the California Energy Commission (CEC) Listing Report

TEMPERATURE RATINGS

Nominal Operating Cell Temperature (NOCT)	+45°C (±2°C)
Temperature Coefficient of P_{max}	-0.39%/°C
Temperature Coefficient of V_{oc}	-0.31%/°C
Temperature Coefficient of I_{sc}	0.045%/°C

MAXIMUM RATINGS

Operational Temperature	-40°C - +85°C
Max System Voltage	1500V (UL / IEC)
Max Series Fuse Rating	15 A

WARRANTY


10 Year Manufacturer's Workmanship Warranty

25 Year Linear Power Guarantee

(Refer to product warranty page for details)

PACKAGING CONFIGURATION

Modules per box:	25 pieces
Modules per 53' trailer:	750 pieces



HELIENE72M/BLK_IFD_1606_1500V